



## TESSAROL acrylic putty for wood

### USE

In the system of wood protection, it is used for the elimination of defects and damages, such as the irregularities, hollows, cracks in the residential areas and outside.

### CHARACTERISTICS

- Very quick drying
- Easy application
- Good sanding
- Eco-friendly

TECHNICAL DATA	
PRODUCT TYPE	acrylic dispersion, pigment, fillers
COLOUR SHADES	white, 3 standard colour shades
TINTING	/
GLOSS	matt
DENSITY	1,7 g / ml
THINNING	ready for use
EU VOC category and limits	IIA(g), 30 g/l (2010); the product contains: max. 20 g/l
PACKAGING	0,75 kg
SHELF LIFE	The shelf life of the originally closed and suitably packed product (temperature from +5°C to +35°C, in dry place) is until the date indicated on packaging. IT SHOULD NOT FREEZE.

INSTRUCTIONS FOR USE	
APPLICATION	spatula
WORKING CONDITIONS	temperature of paint, air and object min. +5°C
DRYING (T = +20°C, rel. hum. 65%)	sanding, new layer after approx. 2 hours At the lower temperature and higher rel. humidity the drying time will prolong.
COVERAGE	depending on the extent of a damage
CLEANING OF TOOLS	immediately after use with water, dried putty with <b>NITRO thinner</b>

### SURFACE PREPARATION

#### Wooden surface

The humidity with soft woods should not exceed 15 %, with hard woods not 12 %. Sand the dry surface and clean, remove waxes, resins and grease with **NITRO thinner**.

### COATING SYSTEMS

SURFACE		SURFACE PREPARATION	IMPREGNATION	PUTTYING	PRIMER	TOP COAT
WOOD	interior	sanding, removal of impurities	/	TESSAROL acrylic putty for wood	1x TESSAROL acrylic primer for wood	wood coatings from the family TESSAROL acrylic
				TESSAROL acrylic putty for wood - colour shades	/	BORI stain
	exterior		1x BORI impregnation	TESSAROL acrylic putty for wood	2x TESSAROL acrylic primer for wood	wood coatings from the family TESSAROL acrylic
				TESSAROL acrylic putty for wood - colour shades	/	BORI stain

### REMARKS AND SPECIFICS

/