



SPEKTRA wall paint for kitchens and bathrooms

USE

For the protection and decoration of interior wall and ceiling surfaces. For a longer period it prevents the growth of mould and algae on the interior wall surfaces in the kitchens, bathrooms, laundries and other spaces, where due to high water vapour concentration the mould and algae are more probably to appear.

It is suitable for the painting of different types of mineral plasters, fibre-cement plates, concrete, plaster-cardboard plates and old coatings.

CHARACTERISTICS

- Vapour permeable
- Less condense formation
- Fungicide protection
- Easy application
- Pleasant odour

TECHNICAL DATA	
PRODUCT TYPE	vinylacetate copolymer dispersion, pigments, fillers and special additives
COLOUR SHADES	white
TINTING	possible with colourants, which are suitable for water-based paints (up to 3%) and with dispersion paints, suitable for tinting
GLOSS	EN 13300 - matt
DENSITY	1,48 - 1,52 kg/l
WASHABILITY	not washable
THINNING	with water up to 5%
EU VOC category and limits	IIA(a), 30 g/l (2010); the product contains: max. 9 g/l
PACKAGING UNITS	5 l
SHELF LIFE	The shelf life of the originally closed and suitably packed product (temperature from +5°C to +35°C, in dry place) is until the date indicated on packaging. IT SHOULD NOT FREEZE !

INSTRUCTIONS FOR USE	
APPLICATION	roller, brush, spraying
WORKING CONDITIONS	min. +5°C air, surface and paint
DRYING (T = +20°C, rel hum. 65%)	the coating is dry and suitable for overcoating after 4 - 6 hours
COVERAGE	theoretically: 5 - 6 m ² with 1 l in 2 coats Practical consumption depending on permeability and surface roughness.
CLEANING OF TOOLS	immediately after use with water

SURFACE PREPARATION

The surface should be free from dust, crumbly particles and other impurities. Remove old falling off coats. Fill up bigger cracks and damaged surface with adequate materials on the mineral basis. Afterwards impregnate with **SPEKTRA acrylic impregnation**. Prior to painting, the surface should be dry and firm.

Apply **SPEKTRA biocide agent SANITOL** to wall surfaces, which are attacked by mould and algae. After the surfaces have dried, remove mould mechanically. Afterwards use **SPEKTRA wall paint for kitchens and bathrooms**.

Paint the spots of nicotine, water outflow, tar, water-proof pencils ... with **SPEKTRA antinicotine paint**, which already represents the final coating

Clean »healthy« surfaces without cracks, which are painted with smooth, shiny or semi-shiny enamels or dispersion paint and sand them with the sanding paper (No. 150).



COATING SYSTEMS

SURFACE	SURFACE PREPARATION	IMPREGNATION	PUTTYING	TOP COAT
New not painted surface - lime-cement plasters - plaster-cardboard plates - concrete and other not porous surfaces		1x SPEKTRA acrylic impregnation 1x SPEKTRA deep impregnation	2x SPEKTRA interior putty (if necessary)	2 - 3x SPEKTRA interior wall paint for kitchens and bathrooms
Painted with dispersion paints - several layers of permeable, not washable coatings - coatings attacked with microorganisms - smooth, shiny, washable coatings	cleaning, removal of crumbly particles, repair of damaged spots 1 - 2x SPEKTRA biocide agent Sanitol , mechanical removal of mould rests cleaning, polishing	1x SPEKTRA acrylic impregnation 1x SPEKTRA acrylic impregnation (if necessary)	2x SPEKTRA interior putty (if necessary)	

REMARKS

- Mix paint thoroughly before use.
- Drying time increases at low temperatures and higher air humidity.
- If you thin paint with a larger quantity of water than recommended, the coverage of a colour film decreases accordingly.
- For a better fungicide effect we recommend to apply paint in two coats.
- We recommend the use of protective gloves.