



SPEKTRA 2000 interior wall paint

USE

For the protection and decoration of interior wall and ceiling surfaces.

It is suitable for the painting of different types of mineral plasters, fibre-cement plates, concrete, plaster-cardboard plates, wall papers from glass fibres, wall papers with relief and old coatings.

CHARACTERISTICS

- High coverage, snow white
- Health and environment friendly paint
- Easy application
- Nice final appearance of the colour film
- Covers already in one coat

TECHNICAL DATA	
PRODUCT TYPE	vinylacetate copolymer dispersion, pigments, fillers and special additives
COLOUR SHADES	white
TINTING	possible with colourantes, which are suitable for water-based paints (up to 3%) and with dispersion paints, suitable for tinting
GLOSS	EN 13300 - matt
DENSITY	1,45 - 1,50 kg/l
WASHABILITY	not washable
THINNING	with water up to 5 %
EU VOC category and limits	IIA(a), 30 g/l (2010); the product contains: max. 22 g/l
PACKAGING	2,5 l, 10 l
SHELF LIFE	The shelf life of the originally closed and suitably packed product (temperature from +5°C to +35°C, dry place) is until the date indicated on packaging. IT SHOULD NOT FREEZE!

INSTRUCTIONS FOR USE	
APPLICATION	roller, brush
WORKING CONDITIONS	min. +5°C air, surface and paint
DRYING (T = +20°C, rel.hum. 65%)	the coating is dry and suitable for overcoating after 4 - 6 hours
COVERAGE	theoretically: 8 - 10 m ² with 1 l (one coat) Practical consumption depending on permeability and surface roughness.
CLEANING OF TOOLS	immediately after use with water

SURFACE PREPARATION

The surface should be free from dust, crumbly particles and other impurities. Remove old falling off coats. Fill up bigger cracks and damaged surface with adequate materials on the mineral basis. Afterwards impregnate with **SPEKTRA acrylic impregnation**. Prior to painting, the surface should be dry and firm.

Apply **SPEKTRA biocide agent SANITOL** to wall surfaces, which are attacked by mould and algae. After the surfaces have dried, remove mould mechanically. Add **SPEKTRA protection against mould** to paint, which for the longer period prevents the growth of microorganisms or use **SPEKTRA wall paint for kitchens and bathrooms**.

Paint the spots of nicotine, water outflow, tar, water-proof pencils... with **SPEKTRA antinicotine paint**, which already represents the final coating. Clean »healthy« surfaces without cracks, which are painted with smooth, shiny or semi-shiny enamels or dispersion paint and sand them with the sanding paper (No. 150).



COATING SYSTEMS

SURFACE	SURFACE PREPARATION	IMPREGNATION	PUTTYING	TOP COAT
New not painted surface - lime-cement plasters - plaster-cardboard plates - concrete and other not porous substrates		1x SPEKTRA acrylic impregnation 1x SPEKTRA deep impregnation	2x SPEKTRA interior putty (if necessary)	1 - 2x SPEKTRA 2000 interior wall paint
Painted with dispersion paints - several layers of permeable, not washable coatings - smooth, shiny, washable coatings	cleaning, removal of crumbly particles, repair of damaged spots cleaning, polishing	1x SPEKTRA acrylic impregnation	2x SPEKTRA interior putty (if necessary)	

REMARKS

- Mix paint thoroughly before use.
- Drying time increases at low temperatures and higher air humidity.
- If you thin paint more than recommended, the coverage decreases.