



SPEKTRA DOMFLOK flakes

USE

The pigmented dry flakes in multi-colour decorative system **SPEKTRA DOMFLOK** for the decoration of the interior wall surfaces in the corridors, halls, waiting rooms, staircases in the public and residential buildings. They are suitable for the combination in the colourless **SPEKTRA DOMFLOK lacquer**.

CHARACTERISTICS

- Numerous colour combinations
- Vivid appearance of interior wall surfaces

TECHNICAL DATA	
PRODUCT TYPE	acrylic pigmented flakes
COLOUR SHADES	colour chart SPEKTRA DOMFLOK (14 colour shades + gold + silver)
PACKAGING	50 g
SHELF LIFE	The shelf life of the originally closed and suitably packed product (temperature from +5°C to +35°C, in dry place) is until the date indicated on packaging. IT SHOULD NOT FREEZE !

INSTRUCTIONS FOR USE	
APPLICATION	brush (flakes mixed into SPEKTRA DOMFLOK lacquer)
WORKING CONDITIONS	min. +5°C air, surface and paint
DRYING (T = +20°C, rel hum. 65%)	the coating is dry and suitable for overcoating after 4 – 6 hours
COVERAGE	50 - 75 g in 1 l of SPEKTRA DOMFLOK lacquer
CLEANING OF TOOLS	immediately after use with water

SURFACE PREPARATION

We apply **SPEKTRA DOMFLOK lacquer** with the mixed in flakes to the surface, which is painted with the selected basic dispersion paint, which must be suitably dry for the enamel application.

COATING SYSTEMS

SURFACE	TOP COAT
2x SPEKTRA DOMFLOK primer or 2x SPEKTRA acrylic facade paint	1x SPEKTRA DOMFLOK lacquer with the mixed in SPEKTRA DOMFLOK flakes

REMARKS

- At first mix the chosen **SPEKTRA DOMFLOK flakes** of different colour shades dry, afterwards mix them with a wooden bar into **SPEKTRA DOMFLOK lacquer**.
- Mix the flakes into the lacquer immediately before the application. We do not recommend a longer storage of the already prepared mixture of flakes and the enamel.
- We combine the flakes colours with the selected colour of the surface.