



## SPEKTRA protection against mould

### USE

The biocide water-based preparation as the fungicide additive to interior and facade dispersion paint for the preventive protection of the painted wall surfaces against the growth of different types of mould and algae. It prevents the growth of microorganisms on the already attacked surfaces.

### CHARACTERISTICS

- Long-term fungicide and algacide protection of the coloured wall surfaces
- Additive to different dispersion paints
- Not harmful to man

TECHNICAL DATA	
PRODUCT TYPE	fungicide / algacide preparation in water
COLOUR SHADES	white, not transparent liquid
TINTING	/
DENSITY	1.0 kg/l
THINNING	/
PACKAGING	1 l
SHELF LIFE	The shelf life of the originally closed and suitably packed product (temperature from +5°C to +35°C, in dry place) is until the date indicated on packaging. IT SHOULD NOT FREEZE !

INSTRUCTIONS FOR USE	
APPLICATION	mixing into dispersion paint
WORKING CONDITIONS	min. +5°C air, surface and paint
COVERAGE	1l in 15l of dispersion paint
CLEANING OF TOOLS	immediately after use with water

### SURFACE PREPARATION

The surface should be free from dust, crumbly particles and other impurities. Remove old falling off coats. Fill up bigger cracks and damaged surface with adequate materials on the mineral basis. Afterwards impregnate with an appropriate impregnation. Prior to painting, the surface should be dry and firm.

Apply **SPEKTRA biocide agent SANITOL** to interior / exterior surfaces, which are attacked by mould and algae. After the surfaces have dried, remove mould mechanically. Add **SPEKTRA protection against mould** to paint, which for the longer period prevents the growth of microorganisms or use **SPEKTRA wall paint for kitchens and bathrooms**.

Paint the spots of nicotine, water outflow, tar, water-proof pencils... with **SPEKTRA antinicotine paint**, which already represents the final coating

Remove saltpetre with brushing and impregnate surface with **SPEKTRA deep impregnation**.

Clean »healthy« surfaces without cracks, which are painted with smooth, shiny or semi-shiny enamels or dispersion paint and sand them with the sanding paper (No. 150).

### COATING SYSTEMS

The procedure for the preparation of surface, impregnation, puttying and painting is stated in technical information of the chosen dispersion paint, to which we add **SPEKTRA protection against mould**.

### REMARKS

- Before the mixing of **SPEKTRA protection against mould**, mix paint thoroughly. The selected dispersion paint should be mixed as well.
- Add **SPEKTRA protection against mould** into the paint during mixing (e.g. with an electric mixer).
- For the efficient biocide protection we recommend to apply two coats of paint, to which you added **SPEKTRA protection against mould**.
- Do not mix **SPEKTRA protection against mould** with biocide preparations of other producers.
- Store out of reach of children
- Do not empty into a sewage system.
- Use the suitable protection gloves.