



SPEKTRA Plus +

USE

For the protection and decoration of interior wall and ceiling surfaces.

Suitable for painting of different types of mineral plasters, fibre-cement plates, concrete, plaster-cardboard plates, wall papers from glass fibres, paper relief wall papers and old coatings.

CHARACTERISTICS

- A good hiding power
- Health and eco-friendly paint
- Easy application
- Nice final appearance of colour film
- Wide selection of colour shades - **HELIOMIX**

TECHNICAL DATA	
COMPOSITION	styrene-acrylate copolymer dispersion, pigment, fillers and special additives
COLOUR SHADES	white, according to colour proposals HELIOMIX (Monicolor Nova 720)
TINTING	HELIOMIX
GLOSS	EN 13300 - matt
DENSITY	1,50 - 1.65 kg/l
WASHABILITY	not washable
THINNING	with water - 15 %
EU VOC category and limits	IIA (a), 30 g/l (2010), product contains: max. 20 g/l
PACKAGING UNITS	2 l, 5l, 10 l
SHELF LIFE /USABILITY	The shelf life of the originally sealed and suitably stored product (temperature from +5°C to +35°C, dry room) is at least until the date as indicated on the packaging. IT SHOULD NOT FREEZE !

INSTRUCTIONS FOR USE	
APPLICATION	roller, brush, spraying
WORKING CONDITIONS	temperature of paint, air and surface min.+5°C
DRYING (T = +20°C, rel. humidity 65%)	dry and suitable for next coat after 4 - 6 hours
COVERAGE	theoretically: 5 - 6 m ² with 1 l in two coats Practical consumption depends on permeability and surface roughness.
CLEANING OF TOOLS	Immediately after use with water

SURFACE PREPARATION

Remove dust, crumbly particles and other impurities from the surface. Remove old plasters, which fall off, fill bigger cracks and the damaged surface parts with suitable materials on mineral basis. We recommend impregnation with **SPEKTRA acrylic impregnation**. Prior to painting the surface should be dry and cured.

Prior to painting paint the wall surfaces, which are attacked with mould and algae with **SPEKTRA biocide agent SANITOL**. After the walls get dry, remove mould mechanically. Add **SPEKTRA protection against mould to the paint** which for a longer period prevents the growth of microorganisms or use **SPEKTRA wall paint for kitchens and bathrooms**.

Remove spots of nicotine, water outflow, tar, water-resistant pencils paint with **SPEKTRA antinicotine paint**, which is already a top coat.

Clean and sand the healthy surfaces without cracks, which are painted with smooth, gloss or semi-gloss enamels or dispersion paints with a sand paper No. 150).



COATING SYSTEMS

SURFACE	SURFACE PREPARATION	PRE	IMPREGNATION	SMOOTHENING	TOP COATS
New not painted surface - lime-cement plasters - plaster- cardboard plates - concrete and other not porous surfaces			1x SPEKTRA acrylic impregnation 1x SPEKTRA deep impregnation	2x SPEKTRA interior putty (if necessary)	2x SPEKTRA Plus +
Painted with dispersion paints - several coats, which are permeable, not washable - smooth, gloss, washable coatings	cleaning, removal of crumbly particles, repair of damaged surface parts, cleaning, sanding		1x SPEKTRA acrylic impregnation	2x SPEKTRA interior putty (if necessary)	

REMARKS AND SPECIFICS

- Mix paint thoroughly before use.
- At low temperatures and higher air humidity the drying time will be prolonged.
- If you thin paint with larger quantity of water than prescribed, the hiding power of a colour film will be reduced accordingly.